

DIRECT-REPLACEMENT  
**FRONT COIL-OVER SHOCKS**  
**REAR SMOOTH BODY SHOCKS**  
INSTALLATION GUIDE



**DODGE 2500/3500 (94+)**

883-24-021 - 2.5 Factory Series Reservoir

883-26-021 - 2.5 Factory Series Reservoir - DSC Adjustable

883-24-023-2.5 Factory Series Reservoir

883-26-023-2.5 Factory Series Reservoir - DSC Adjustable

883-24-025-2.5 Factory Series Reservoir

883-26-025-2.5 Factory Series Reservoir - DSC Adjustable

883-24-022 - 2.5 Factory Series Reservoir

883-26-022 - 2.5 Factory Series Reservoir - DSC Adjustable

883-24-024-2.5 Factory Series Reservoir

883-26-024-2.5 Factory Series Reservoir - DSC Adjustable

883-24-026-2.5 Factory Series Reservoir

883-26-026-2.5 Factory Series Reservoir - DSC Adjustable



## DODGE 2500/3500 (94+)

883-24-021 - 2.5 Factory Series Reservoir

883-26-021 - 2.5 Factory Series Reservoir - DSC Adjustable

883-24-023-2.5 Factory Series Reservoir

883-26-023-2.5 Factory Series Reservoir - DSC Adjustable

883-24-025-2.5 Factory Series Reservoir

883-26-025-2.5 Factory Series Reservoir - DSC Adjustable

883-24-022 - 2.5 Factory Series Reservoir

883-26-022 - 2.5 Factory Series Reservoir - DSC Adjustable

883-24-024-2.5 Factory Series Reservoir

883-26-024-2.5 Factory Series Reservoir - DSC Adjustable

883-24-026-2.5 Factory Series Reservoir

883-26-026-2.5 Factory Series Reservoir - DSC Adjustable

## INSTALLATION GUIDE

Thank you for choosing FOX direct-replacement, coil-over shocks for your vehicle. FOX products are designed, tested, and manufactured by the finest professionals in the industry.

FOX recommends that you become completely familiar with the handling characteristics of your modified vehicle before operating it under rigorous conditions, helping to avoid potential rollover situations and other loss of control events. FOX further recommends that you use appropriate protective equipment at all times when operating your vehicle.

To achieve the best performance and product longevity, periodic service and maintenance is required. Please refer to the Service and Upgrades section for more information.

## WARNINGS

- FOX direct-replacement, coil-over shocks should always be installed as a pair for maximum performance.
  - Proper installation and service procedures are essential for the safe and reliable installation of chassis parts, requiring the experience and tools specially designed for this purpose. Installation and maintenance procedures for this product must be performed by a qualified service technician, to avoid potentially unsafe vehicle handling characteristics, which may result in **SERIOUS INJURY** or **DEATH**.
  - Modifying your vehicle's suspension will change the handling characteristics of your vehicle. Under certain conditions, your modified vehicle may be more susceptible to loss of control or rollover, which can result in **SERIOUS INJURY** or **DEATH**. Thoroughly familiarize yourself with the modified vehicle handling characteristics before any rigorous vehicle operation. Wear body protective gear including head protection when appropriate.
- Installation of vehicle roll bars or cage is highly recommended.
- FOX direct-replacement, coil-over remote reservoir shocks are gas-charged and are highly pressurized. Placing shocks in a vise or clamp, applying heat, or attempting to open or service the shock without the proper tools and training can result in **SERIOUS INJURY** or **DEATH**. Do not attempt to modify, puncture or incinerate a FOX direct-replacement, coil-over shock absorber.
  - Any attempt to misuse, misapply, modify, or tamper with any FOX product voids any warranty and may result in **SERIOUS INJURY** or **DEATH**.

## GUIDELINES

- Always use a chassis lift for the installation of shocks, and make certain that the raised vehicle is securely attached to the lift to prevent the vehicle from slipping, falling, or moving during the installation process.
- **DO NOT** install any FOX product without the necessary special tools, expertise and chassis lift, or you will subject yourself to the risk of **SERIOUS**

INJURY or DEATH. If you elect to not use a chassis lift (which election may result in SERIOUS INJURY or DEATH), ensure that the vehicle is on level ground, that all tires on the ground during installation are blocked to prevent vehicle movement, that at least two tires are on the ground at all times, and that adequately secured jack stands are used to support the vehicle. NEVER get under the vehicle until you have checked to ensure that the vehicle will be stable during installation.

- FOX direct-replacement, coil-over shocks are designed to fit your vehicle's shock mounts with no modifications with the exception of reservoir placement on specific models and applications.

## INSTRUCTIONS - FRONT

Medium-strength thread-lock (blue Loctite) is recommended on all bolts.

1. With the vehicle on the ground, remove both fender liners. Make sure to disconnect any sensors/plugs from fender liners before removal.
2. Remove any brake line brackets from each side of vehicle frame.
3. Disconnect the sway bar from vehicle by removing the (4) bolts securing it to vehicle frame.
4. Disconnect the track bar from the driver side mount.(Fig. 1)
5. Disconnect upper shock mounting by removing nut and washer/bushing from the shock and the (3) flange nuts that secure the shock tower to vehicle frame. (Do not discard flange nuts and upper shock tower as they will be reused with your new FOX shock.)
6. Lift the vehicle, please read the installation guidelines for instructions on how to properly lift and secure the vehicle.
7. Remove both front wheels.

8. Disconnect stock shock from lower mount and remove from vehicle. (Do not discard bolt and nut, as it will be used with your new shock.
9. Remove coil springs.
10. For ease of reinstallation of springs, separate the stud ring from the spring assembly and reattach to coil bucket with the (3) flange nuts (Do not install shock tower yet).
11. Install new shock by feeding it through the engine bay into the coil bucket. While sliding shock into position, reinstall coil spring at the same time.
12. Connect shock to lower mount and torque to factory specifications.
13. Using the supplied stem mount hardware, install (1) washer and (1) bushing onto the shock stem.

14. Once the spring has pressure on stud ring, remove the flange nuts securing it and reinstall shock tower. For external reservoir models, make sure reservoir is facing toward the front of the vehicle and through the shock tower opening. Install supplied reservoir bracket onto center stud toward the outside of the vehicle (Fig 2). Torque flange nuts to factory specifications.
15. Connect shock with supplied stem mount washer, bushing, and nut on top of the shock tower. Tighten nut until 5/8" of total stem is showing.
16. On external reservoir models, mount the reservoir onto the reservoir bracket with the supplied hose clamps. Utilize the slots in the brackets to locate clamps. Do not feed the clamps



Fig. 1: Track bar removal



Fig. 2: Passenger side



Fig. 3: Driver side

through the slots in the brackets.(Fig. 3)

17. Reinstall both front wheels and torque to factory specifications.
18. Reinstall sway bar and track bar, torque to factory specifications.
19. Reinstall brake line brackets and fender liners, torque to factory specifications.
20. Check that suspension has proper clearance by steering in both directions.

## INSTRUCTIONS - REAR

Medium-strength thread-lock (blue Loctite) is recommended on all bolts.

1. Please read the installation guidelines for instructions on how to properly lift and secure the vehicle.
2. Remove the shock shocks. It may be necessary to support or raise the vehicle axle in order to remove bolts and for installation of new shock. (Do not discard bolts and nuts as they will be used with your new FOX shocks.)
3. Install new FOX shock. For piggy back reservoir models, make sure reservoir is pointing toward the front of the vehicle on both driver and passenger sides (Fig. 4). Torque to factory specifications.



Fig. 4: Driver side

## FOX LIMITED WARRANTY

FOX Factory, Inc., a California corporation having offices at 130 Hangar Way, Watsonville, CA 95076 ("FOX"), makes the following LIMITED WARRANTY with respect to its suspension products:

### LIMITED ONE (1) YEAR WARRANTY ON SUSPENSION PRODUCTS

Subject to the limitations, terms and conditions hereof, FOX warrants, to the original retail owner of each new FOX suspension product, that the FOX suspension product, when new, is free from defects in materials and workmanship. Unless otherwise required by law, this warranty expires one (1) year from the date of the original FOX suspension product retail purchase from an authorized FOX dealer or from a FOX authorized Original Equipment Manufacturer where FOX suspension is included as original equipment on a purchased vehicle. If law requires a warranty duration of greater than one (1) year, then, subject to the other provisions hereof, this warranty will expire at the end of the minimum warranty period required by such law.

## TERMS OF WARRANTY

This warranty is conditioned on the FOX suspension product being operated under normal conditions and properly maintained as specified by FOX. This warranty is only applicable to FOX suspensions purchased new from an authorized FOX source and is made only to the original retail owner of the new FOX suspension product and is not transferable to subsequent owners. This warranty is void if the FOX suspension product is subjected to abuse, neglect, improper or unauthorized repair, improper or unauthorized service or maintenance, alteration, modification, accident or other abnormal, excessive, or improper use.

Should it be determined by FOX in its sole and final discretion, that a FOX suspension product is covered by this warranty, it will be repaired or replaced, by a comparable model, at FOX's sole option, which will be conclusive and binding. THIS IS THE EXCLUSIVE REMEDY UNDER THIS WARRANTY. ANY AND ALL OTHER REMEDIES AND DAMAGES THAT MAY OTHERWISE BE APPLICABLE ARE EXCLUDED, INCLUDING, BUT NOT LIMITED TO,



INCIDENTAL OR CONSEQUENTIAL DAMAGES OR PUNATIVE DAMAGES.

This limited warranty does not apply to normal wear and tear, malfunctions or failures that result from abuse, improper assembly, neglect, alteration, improper maintenance, crash, misuse or collision. This limited warranty gives the consumer specific legal rights. The consumer may also have other legal rights which vary from state to state or country to country. Some states and countries do not allow the exclusion or limitation of incidental or consequential damages or warranties, and if dictated by law the above limitations or exclusions may not apply to you. If it is determined by a court of competent jurisdiction that a certain provision of this limited warranty does not apply, such determination shall not affect any other provision of this limited warranty and all other provisions shall remain in full effect.

THIS IS THE ONLY WARRANTY MADE BY FOX ON ITS SUSPENSION PRODUCTS AND COMPONENTS, AND THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION HEREIN. ANY WARRANTIES THAT MAY OTHERWISE BE IMPLIED BY

LAW INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED.

# SHOX NEED ♥ TOO

## SERVICE & UPGRADES

Have your FOX serviced or upgraded by FOX technicians. Call our Offroad and Truck Service Center at 619.768.1800 to go over the service and upgrade options available for your shocks. Once you've setup your service or upgrades you will receive a return authorization number and shipping instructions.

## SERVICE MENUS & PRICING

Please visit [foxshox.info/orservice](http://foxshox.info/orservice)



## SERVICE INTERVALS

- 100% street use: every 50,000 miles
- 50% street / 50% offroad use: every 10,000 miles



VISIT [RIDEFOX.COM/TRUCK](http://RIDEFOX.COM/TRUCK)  
TO FIND FOX OFFERINGS FOR  
YOUR TRUCK OR SUV

## RACE PERFORMANCE FOR YOUR DAILY DRIVER

# 2.0 PERFORMANCE SERIES IFP SHOCK

### REPLACE YOUR STOCK SHOCKS WITH RACE- WINNING TECHNOLOGY

### HEAT-REDUCING DESIGN

- » Cold-forged, metal-impacted 6061 T6 aluminum shock body dissipates heat three times faster than a conventional steel body shock. The 2.0 Performance Series shock runs as cool as a 2.5 diameter shock on the same application.
- » FOX formulated race shock oil developed for ultimate performance at variable temperatures.

### APPLICATION- SPECIFIC VALVING

- » During development we rigorously tested to maximize offroad performance by utilizing the same proprietary deburred valve shims and high-flow piston design that is found in FOX race products.

### TOUGH FINISH

- » CNC machined aluminum components are Type II hard anodized to a scratch- and fade-free black finish.
- » Heavy-duty 5/8" chrome shafts are induction case hardened to over 55 Rockwell C, virtually eliminating scratches caused by roost and debris.

### FADE-FREE PERFORMANCE

- » The Internal Floating Piston (IFP) design separates shock oil from the high-pressure nitrogen charged gas chamber, eliminating oil aeration and cavitation, while providing a predictable ride — capable of handling the roughest conditions with fade-free performance.



# STAY INFORMED

## REGISTER YOUR PRODUCT



- 1 Create your personal profile
- 2 Let us know which products you own
- 3 Receive special offers on service, upgrades, and product



RIDEFOX.COM 750 VERNON WAY SUITE 101. EL CAJON, CA 92020 USA  
1.800.FOX.SHOX (369.7469) 619.768.1800 ORSERVICE@RIDEFOX.COM

PN 605-01-133 REV A MAY 2014