



**DIRECT-REPLACEMENT
INSTALLATION GUIDE**

JEEP JK

ATS STABILIZER

JEEP JK (2007-2018)

983-02-070 - 2.0 PERFORMANCE SERIES ATS Stabilizer - Stock & 1-3/8" Tie Rod

983-02-142 - 2.0 FACTORY RACE SERIES ATS Stabilizer - 1-1/2" Tie Rod

983-02-145 - 2.0 FACTORY RACE SERIES ATS Stabilizer - Stock & 1-3/8" Tie Rod

983-02-146 - 2.0 FACTORY RACE SERIES ATS Stabilizer - 1-5/8" Tie Rod

985-02-121 - 2.0 PERFORMANCE SERIES TS Stabilizer - Stock & 1-3/8" Tie Rod

985-02-122 - 2.0 PERFORMANCE SERIES TS Stabilizer - 1-5/8" Tie Rod

985-02-128 - 2.0 PERFORMANCE SERIES TS Stabilizer - 1-1/2" Tie Rod

CONTENTS

INTRODUCTION	1
SUPPLIED PARTS	2
SHOCK DIAGRAM	3
SAFETY INSTRUCTIONS	4
INSTALLATION GUIDELINES	5
STABILIZER SHOCK INSTALLATION	6
WARRANTY INFORMATION	9
SHOCKS NEED LOVE TOO	10

INTRODUCTION

Thank you for choosing FOX direct-replacement, shocks for your vehicle. FOX products are designed, tested, and manufactured by the finest professionals in the industry.

FOX recommends that you become completely familiar with the handling characteristics of your modified vehicle before operating it under rigorous conditions, helping to avoid potential rollover situations and other loss of control events. FOX further recommends that you use appropriate protective equipment at all times when operating your vehicle.

To achieve the best performance and product longevity, periodic service and maintenance is required. Please refer to the Service and Upgrades section for more information.

IN THE BOX

- Mounting Hardware
- Steering Stabilizer
- Installation Manual


SUPPLIED PARTS

STABILIZER ASSEMBLY				
FOX PN	DESCRIPTION		QTY	NOTES
983-02-070	ATS STEERING STABILIZER		1	Stock & 1-3/8" Tie Rod
983-02-142	ATS STEERING STABILIZER		1	1-1/2" Tie Rod
983-02-145	ATS STEERING STABILIZER		1	Stock & 1-3/8" Tie Rod
983-02-146	ATS STEERING STABILIZER		1	1-5/8" Tie Rod
985-02-121	TS STEERING STABILIZER		1	Stock & 1-3/8" Tie Rod
985-02-122	TS STEERING STABILIZER		1	1-5/8" Tie Rod
985-02-128	TS STEERING STABILIZER		1	1-1/2" Tie Rod
MOUNTING HARDWARE				
FOX PN	DESCRIPTION	*HARDWARE REF.	QTY	NOTES
026-05-086	TRACK BAR BOLT: M14-1.5, 1/2-20	A1	1	Mounts eyelet end of the stabilizer.
018-00-026-A	LOCK NUT: 1/2-20 x 0.597	A2	1	
018-05-046	WASHER: M14	A3	1	
026-01-102-1	TIE ROD CLAMP TOP	B1	1	Stock & 1-3/8" Tie Rod Clamp mounts the stabilizer to the track bar of the vehicle.
026-01-102-2	TIE ROD CLAMP BOTTOM	B2	1	
026-01-103-1	TIE ROD CLAMP TOP	B1	1	1-1/2" Tie Rod Clamp mounts the stabilizer to the track bar of the vehicle.
026-01-103-2	TIE ROD CLAMP BOTTOM	B2	1	
026-01-104-1	TIE ROD CLAMP TOP	B1	1	1-5/8" Tie Rod Clamp mounts the stabilizer to the track bar of the vehicle.
026-01-104-2	TIE ROD CLAMP BOTTOM	B2	1	
018-02-046	SCREW: 1/4"-20 X 1.25"	B3	4	The tie rod clamp uses 4 screws.


*Hardware Reference is used throughout the installation manual to provide notation of the supplied kit.

SHOCK DIAGRAM

ATS STABILIZER



TS STABILIZER



PART NO.	NAME	PART NO.	NAME
1	Eyelet	6	Shock Body
2	Reservoir Bridge	7	Schrader Valve
3	Reservoir	8	Adjuster Screw
4	Wiper Seal	9	Pinch Bolt
5	Shaft	10	Tie Rod Clamp

WARNING

SAFETY INSTRUCTIONS

- FOX direct-replacement shocks are designed to fit and allow proper clearance with the factory suspension. If aftermarket suspension components are installed it is the customers responsibility to ensure that at full cycle the suspension clears the FOX shocks.
- FOX direct-replacement shocks should always be installed as a set for maximum performance.
- Proper installation and service procedures are essential for the safe and reliable operation of the suspension components, requiring the experience and tools specially designed for this purpose. Installation and maintenance procedures for this product must be performed by a qualified service technician, to avoid potentially unsafe vehicle handling characteristics, which may result in **SERIOUS INJURY** or **DEATH**.
- Modifying your vehicle's suspension will change the handling characteristics of your vehicle. Under certain conditions, your modified vehicle may be more susceptible to loss of control or rollover, which can result in **SERIOUS INJURY** or **DEATH**. Thoroughly familiarize yourself with the modified vehicle handling characteristics before any rigorous vehicle operation. Wear protective body gear and a helmet when appropriate. Installation of vehicle roll bars or cage is highly recommended.
- FOX direct-replacement shocks are gas-charged and are highly pressurized. Placing shocks in a vise or clamp, applying heat, or attempting to open or service the shock without the proper tools and training can result in **SERIOUS INJURY** or **DEATH**. Do not attempt to modify, puncture or incinerate a FOX direct-replacement shock absorber.
- Any attempt to misuse, misapply, modify, or tamper with any FOX product voids any warranty and may result in **SERIOUS INJURY** or **DEATH**.

WARNING

INSTALLATION GUIDELINES

- Always use a chassis lift for the installation of shocks, and make certain that the raised vehicle is securely attached to the lift to prevent the vehicle from slipping, falling, or moving during the installation process.
- DO NOT install any FOX product without the necessary special tools, expertise and chassis lift or you will subject yourself to the risk of SERIOUS INJURY or DEATH. If you elect to not use a chassis lift (which may result in SERIOUS INJURY or DEATH), ensure that the vehicle is: (1) on level ground, (2) that all tires on the ground during installation are blocked to prevent vehicle movement, (3) that at least two tires are on the ground at all times, and (4) that adequately secured jack stands are used to support the vehicle. NEVER get under the vehicle until you have checked to ensure that the vehicle will be stable during installation.
- FOX direct-replacement shocks are designed to fit your vehicle's shock mounts without modification except the reservoir placement on specific models and applications.

STABILIZER SHOCK INSTALLATION

TOOLS REQUIRED

- Manufacturer Torque Specs
- Torque Wrench
- Medium-Strength Thread-Lock

STOCK STABILIZER REMOVAL

NOTICE: Medium-strength thread-lock is recommended on all bolts.

1. Please read the INSTALLATION GUIDELINES on page 5 for instructions on how to properly lift and secure the vehicle.

NOTICE: Ensure vehicle is at full droop during installation.

2. Remove the stock steering stabilizer and tie rod bracket.

FOX STABILIZER INSTALLATION

3. Replace the stock track bar bolt with supplied Group A bolt (Fig. 1).




Fig. 1: Install the Group A track bar bolt.

4. Compress the stabilizer so 1/4" of shaft is exposed between the eyelet and shock body. For ATS models, turning the adjuster screw on the eyelet fully counter clockwise will make compressing the stabilizer easier (Fig. 2).




Fig. 2: Eyelet installed with 1/4" of shaft exposed.

5. Install eyelet end of stabilizer on the track bar bolt. Use the Group A washer and nut. Make sure adjuster screw is pointed down. Torque nut to 60 ft-lb (Fig. 3).



Fig. 3: Eyelet installed on track bar bolt.

6. Turn the vehicle's wheels completely to the right so they rest against the steering stops.

7. Loosely mount the Group B tie rod clamp to the track bar with the Group B hardware (Fig. 4).



Fig. 4: Loosely clamp the stabilizer to the track bar.

8. Orient the stabilizer to avoid interference with any parts of the vehicle (suspension, driveline, engine, etc.) through the entire range of steering and suspension travel.

9. If interference issues exist and cannot be resolved by rotating the tie rod clamp, rotate the stabilizer reservoir. If installing stabilizer on 2012 and newer model with stock suspension or with less than a 2.5" lift and aftermarket 1 1/4" bump stop extension, the stabilizer reservoir must be rotated for clearance. Loosen the pinch bolt on the L-bracket between the stabilizer and track bar clamp, rotate reservoir approximately 135 degrees down and toward rear of vehicle. Torque pinch bolt to 12 lb-ft. (Fig. 5).




Fig. 5: 135 degree reservoir orientation on some 2012 and newer applications.

10. With the wheels turned fully to the right and 1/4" of shaft exposed on the stabilizer, tighten the tie rod clamp bolts to 12 lb-ft.

CHECK AND FINAL DETAILS

11. Check that the vehicle steers completely in both directions and is limited by the steering stops, not the stabilizer.

12. Place vehicle on the ground and check that the steering stabilizer does not interfere with anything (suspension, driveline, engine, etc.) through entire range of steering and suspension travel.

NOTICE: If after installing the steering stabilizer a vehicle lift is added or maintenance is performed requiring the removal of the stabilizer (such as a wheel alignment), you must re-mount the tie rod clamp at the vehicle's new full droop height. Use the same steps outlined above to complete the clamp re-mount.

WARRANTY INFORMATION

FOX LIMITED WARRANTY

FOX Factory, Inc., a Georgia corporation having an office at 6634 Highway 53 Braselton, GA 30517 (“FOX”), makes the following LIMITED WARRANTY with respect to its suspension products:
LIMITED ONE (1) YEAR WARRANTY ON SUSPENSION PRODUCTS.

Subject to the limitations, terms and conditions hereof, FOX warrants, to the original retail owner of each new FOX suspension product, that the FOX suspension product, when new, is free from defects in materials and workmanship. Unless otherwise required by law, this warranty expires one (1) year from the date of the original FOX suspension product retail purchase from an authorized FOX dealer or from a FOX authorized Original Equipment Manufacturer where FOX suspension is included as original equipment on a purchased vehicle. If law requires a warranty duration of greater than one (1) year, then, subject to the other provisions hereof, this warranty will expire at the end of the minimum warranty period required by such law.

TERMS OF WARRANTY

This warranty is conditioned on the FOX suspension product being operated under normal conditions and properly maintained as specified by FOX. This warranty is only applicable to FOX suspensions purchased new from an authorized FOX source and is made only to the original retail owner of the new FOX suspension product and is not transferable to subsequent owners. This warranty is void if the FOX suspension product is subjected to abuse, neglect, improper or unauthorized repair, improper or unauthorized service or maintenance, alteration, modification, accident or other abnormal, excessive, or improper use.

Should it be determined by FOX in its sole and final discretion, that a FOX suspension product is covered by this warranty, it will be repaired or replaced, by a comparable model, at FOX’s sole option, which will be conclusive and binding. THIS IS THE EXCLUSIVE REMEDY UNDER THIS WARRANTY. ANY AND ALL OTHER REMEDIES AND DAMAGES THAT MAY OTHERWISE BE APPLICABLE ARE EXCLUDED, INCLUDING, BUT NOT LIMITED TO, INCIDENTAL OR CONSEQUENTIAL DAMAGES OR PUNITIVE DAMAGES.

This limited warranty does not apply to normal wear and tear, malfunctions or failures that result from abuse, improper assembly, neglect, alteration, improper maintenance, crash, misuse or collision. This limited warranty gives the consumer specific legal rights. The consumer may also have other legal rights which vary from state to state or country to country. Some states and countries do not allow the exclusion or limitation of incidental or consequential damages or warranties, and if dictated by law the above limitations or exclusions may not apply to you. If it is determined by a court of competent jurisdiction that a certain provision of this limited warranty does not apply, such determination shall not affect any other provision of this limited warranty and all other provisions shall remain in full effect.

THIS IS THE ONLY WARRANTY MADE BY FOX ON ITS SUSPENSION PRODUCTS AND COMPONENTS, AND THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION HEREIN. ANY WARRANTIES THAT MAY OTHERWISE BE IMPLIED BY LAW INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED.

SHOCKS NEED LOVE TOO

FOX SERVICE AND UPGRADES

HAVE YOUR FOX SHOCKS SERVICED BY FOX TECHNICIANS. CALL OUR OFF-ROAD AND TRUCK SERVICE CENTER AT 619.768.1800 TO GO OVER THE SERVICE AND UPGRADE OPTIONS AVAILABLE FOR YOUR PRODUCT. ONCE YOU'VE SETUP YOUR SERVICE AND/OR UPGRADES YOU WILL RECEIVE A RETURN AUTHORIZATION NUMBER AND SHIPPING INSTRUCTIONS.

COMPLETE SERVICES

100% street use: every 50,000 miles

50% street/ 50% off-road use: Every 10,000 miles

SERVICE MENUS AND PRICING

visit ridefox.com/service



**WARNING: Cancer and
Reproductive Harm –**
www.P65Warnings.ca.gov

